



Flow Characteristics Chart HKD SV10201 Snowgun

	Cold Configuration				Moderate Configuration				Marginal Configuration			
Top Nozzle Type	2520	2520	2520	2520	2515	2515	2515	2515	2510	2510	2510	2510
Valve 1 Nozzle Type	2540	OFF	2540	OFF	2520	OFF	2520	OFF	2515	OFF	2515	OFF
Middle Nozzle Type	2520	2520	2520	2520	2515	2515	2515	2515	2510	2510	2510	2510
Nucleator Nozzle Type	6580	6580	6580	6580	6580	6580	6580	6580	6580	6580	6580	6580
Valve 2 Nozzle Type	2560	2560	OFF	OFF	2540	2540	OFF	OFF	2520	2520	OFF	OFF
Water Pressure (PSI)	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM	Flow GPM
180	59	43	35	19	39	31	23	14	25	19	17	10
200	63	45	37	20	41	33	24	15	26	20	17	11
220	66	48	39	21	43	34	25	16	27	21	18	12
240	69	50	41	22	45	36	26	17	29	22	19	12
260	72	52	42	23	47	37	28	18	30	23	20	13
280	75	54	44	24	49	39	29	18	31	24	21	13
300	78	56	46	24	51	40	30	19	32	24	22	14
320	80	58	47	25	53	42	31	20	34	25	22	14
340	83	60	49	26	55	43	32	20	35	26	23	15
360	86	62	50	27	56	44	33	21	36	27	24	15
380	88	64	52	28	58	46	34	22	37	28	25	15
400	90	66	53	28	59	47	35	22	38	28	25	16
420	93	67	55	29	61	48	35	23	39	29	26	16
440	95	69	56	30	62	49	36	23	40	30	26	17
460	97	70	57	30	64	50	37	24	40	30	27	17
480	99	72	58	31	65	52	38	24	41	31	28	17
500	101	74	60	32	67	53	39	25	42	32	28	18
520	104	75	61	32	68	54	40	25	43	32	29	18
550	107	77	63	33	70	55	41	26	44	33	30	19
570	109	79	64	34	71	56	41	27	45	34	30	19
590	110	80	65	35	73	57	42	27	46	35	31	19
610	112	82	66	35	74	58	43	27	47	35	31	20
630	114	83	67	36	75	59	44	28	48	36	32	20
650	116	84	68	36	76	60	44	28	48	36	32	20
670	118	86	69	37	77	61	45	29	49	37	33	21
690	120	87	70	37	79	62	46	29	50	37	33	21
710	121	88	71	38	80	63	46	30	51	38	34	21